SOPRA N°2

Product data sheet



Sopra $N^{\circ}2$ pushes back the limits of sound reproduction in terms of transparency in a very compact enclosure. This loudspeaker is equipped with best midrange drivers ever developed by Focal, with the NIC (Neutral Inductance Circuit) and TMD* (Tuned Mass Damper) technologies. Compact, modern, pure design, character...: all these essential factors are also combined to ensure perfect integration into your interior. Sopra $N^{\circ}2$ is perfectly at ease in rooms measuring up to 320ft^2 (30m^2), and is even ideal for larger rooms measuring up to 750ft^2 (70m^2).



Key points

- Midrange driver with TMD® suspension and NIC magnetic circuit
- IHL Beryllium tweeter (Infinite Horn Loading)
- Drivers developped and manufactured by Focal in France

Туре	Three-way Bass-reflex floorstanding loudspeaker
Drivers	2 x 7" (18cm) "W" woofer 6½" (16.5cm) "W" midrange with TMD® suspension, NIC motor 1" (27mm) IHL Beryllium inverted dome tweeter
Frequency response (+/- 3dB)	34Hz - 40kHz
Low frequency point - 6dB	28Hz
Sensivity (2.83V / 1m)	91dB
Nom. impedance	8 Ω
Minimum impedance	3.1 Ω
Crossover frequency	250Hz / 2 200Hz
Recommended amplifier power	40 - 300W
Dimensions (HxLxP)	46 ^{7/8} x 14 ^{1/8} x 21 ^{1/4} (119 x 35,8 x 54 cm)
Net weight	122lbs (55kg)



